

# Antirutschmatte Cushion Dek (TM) Grip Step



- Aggressive slip resistant surfaces with abrasive anti-slip coating.
- Slot perforations (13 mm x 48 mm) facilitate drainage of fluids, keeping the surface clean.
- Designed to withstand harsh chemicals, this mat offers simple solutions to almost any industrial or foodservice application.
- Made of tough PVC compound, designed to yield a long service life and resist to industrial oils.
- Easy roll-up and clean-up.
- Free of silicone therefore safe for vehicle painting facilities.
- Ergonomic benefit of 11 mm thickness worker platform
- Top surface with raised pyramid configuration enhances traction while channeling liquids.
- Free of toxic DOP and DMF.

PRODUCT SPECIFICATIONS		
Designation	Industrial Matting	
Type	Anti-slip	
Description	Duckboard, pyramid configured top surface with slotted perforations, resistant to industrial oil	
Material	100% PVC	
Process	Injection moulding	
Category	Good	
Recommended use	Medium duty – industrial environments, wet/dry areas – extremely slippery areas	
Colours	Black	
Weight	6.5 kg/m <sup>2</sup>	
Thickness	11 mm	
Standard sizes	91 cm x 122 cm 91 cm x 182 cm 91 cm x 300 cm 91 cm x 10 m	
Custom sizes	60 cm, 91 cm, 122 cm, 182 cm per linear meter	
Special remarks	With Grip Step® abrasive anti-slip coating	
PRODUCT TESTING		
Tests	Norms	Results
Compression deflection	U.S.	
	1.4 kg/cm <sup>2</sup>	1.82 cm
	2.8 kg/cm <sup>2</sup>	1.66 cm
Foam battery	ASTM D3574	
Abrasion resistance	ASTM D3884-01	
	500 Cycles	
	5000 Cycles	0.57
Static coefficient of friction	ASTM C1028-96	
Elongation	ASTM D412	
Breaking load	ASTM D412	
Graves tear strength	ASTM D 1004	
Hardness	ASTM D2240-02	
Anti-slip	DIN 51130 and BG-RULE BGR181	
FIRE TESTING		
	Critical radiant flux	ASTM E-648
	Fire retardancy	DIN4102 EN 13501-1
	Flammability test	ASTM D2859
ESD	ANSI ESD S7.1 50% Humidity	
Sustainability	<ul style="list-style-type: none"> <li>• Recyclable material</li> <li>• Reach Compliant (Registration, Evaluation, Authorization and Restriction of Chemicals)</li> </ul>	

Zu beziehen bei:

<https://matten.center>, [info@matten.center](mailto:info@matten.center), Tel. 0049 63 59 96 11 906